



FEATURES:

- Exceptional effective non-toxic fire extinguishing agent
- Uniquely easy to install and Maintain
- Certified according to CEN/TR 15276-1, NEN-ISO 15779, UL 2775 and BRL K23001
- Approved by EPA for SNAP listing
- Ecologically safe and environmentally friendly (O.D.P.=0, G.W.P.=0)
- Very cost efficient


Description

DSPA aerosol generators can be used as a part of a highly effective fixed extinguishing system. A DSPA generator is non-pressurized and is installed inside a room or compartment that requires protection. After activation, an aerosol cloud is generated, which expands volumetrically, flooding the space and extinguishing the fire. The DSPA generators are mainly designed to use in normally unoccupied and unoccupied areas and are effective on class A, B, C fires.

Application

The DSPA generator 11-4 is recommended for the protection of semi large compartments such as storage rooms, archives, technical rooms and server rooms.

Specifications

Model	11-4
Part Number	DSPA-ART00014
Dimensions	165 x 72 mm
Total weight	2000 g
Compound weight	900 g
Volume coverage	7 - 21 m ³
Discharge time	25 sec
Activation, current	Built-in starter, 1.3A
Operation conditions	-40°C to 75°C/ Up to 95% RH at 54°C
Colour	Standard RAL 3000, other colours upon request
Min. distance for persons(75°C) from discharge outlet	
Min. distance for combustible material(200°C) from discharge outlet	
Min. distance for construction structures(400°C) from discharge outlet	

More information:

DSPA.nl
 Postbus 6572
 6503 GB Nijmegen
 The Netherlands
 T. +31 (0) 24 35 22 573
 F. +31 (0) 24 37 87 583
 E info@dspa.nl



Datasheet: DSPA GENERATOR
 Serie: 11-4
 Version: 1.2
 Date: 15-10-2012